



PROROC® REGULAR GYPSUM BOARD

FOR USE ON INTERIOR WALLS AND CEILINGS

OVERVIEW

Also referred to as drywall or gypsum board, ProRoc® Regular is a lightweight, durable, cost-effective building material designed for use in interior ceilings or walls. The core is manufactured using premium quality, noncombustible gypsum.

ProRoc® Regular gypsum board is covered by a smooth front face and back covering paper—made from 100% recycled material. The edges have been precisely manufactured in a tapered fashion and paper-bound to facilitate no-hassle joint finishing. After applying a primer, the board can given a number of decorative treatments, including paint, texture, or wallpaper. ProRoc® Regular is the perfect gypsum board to finish interior ceilings and walls.

PRODUCT DATA:

ASTM C 1396

Thickness: 1/4" (6.4 mm) - 8' Length, 3/8" (9.5 mm) - 8' Length, 1/2" (12.7 mm)

Lengths: 7' (2140 mm), 8' (2440 mm), 8' 6" (2590 mm), 9' (2740 mm), 10' (3050 mm), 12' (3660 mm), 14' (4270 mm), 15' (4570 mm), 16' (4880 mm)

Widths: 4' (1220 mm) standard, 54" (1370 mm) - 8', 10', 12' and 14' Lengths

Edges: Tapered

Paper: 100% recycled Ivory colored face paper and strong liner back paper.

Weight: 1/4" (6.4 mm): 1.13 lb/ft² (5.5 kg/m²), 3/8" (9.5 mm): 1.25 lb/ft² (6.1 kg/m²), 1/2" (12.7 mm): 1.6 lb/ft² (7.8 kg/m²)

Packaging: Two pieces per bundle; face-to-face and end-taped.

Please see the [Product Data and Submittal Sheet](#) for a complete description.

Gypsum Board Brochure:

- [US](#)
- [Canada](#)

TECHNICAL INFORMATION

You may be able to order special edges, lengths, and widths—contact your CertainTeed sales representative.

Core: ProRoc® Gypsum Board Products are manufactured from noncombustible, natural, premium quality (mined) gypsum, recycled gypsum and DSG (from FGD, flue gas desulphurisation).

Applicable Standards: ASTM C 1396

Please see the [Product Data and Submittal Sheet](#) for complete Technical Data.



Other resources:

[MSDS - Gypsum Board](#)

[3-Part Spec - Gypsum Board](#)

INSTALLATION

Most paints, textures, and wall coverings can be applied to CertainTeed ProRoc® Regular Gypsum Board. A full-bodied latex primer must be applied before the application of any final decorative covering; doing so equalizes the suction between the board's paper surfacing and the joint compounds. To achieve optimal results, every surface—joint compounds included—should be free of dust, non-glossy, and clean. With the use of glossy paints, it is recommended that a thin skim coat of compound be applied over the whole surface, Level 5 finish. This minimizes joint photographing or highlighting. The same recommendation applies in areas of critical sidelighting of artificial or natural light. It is also recommended to apply sealer under wall paper or other coverings to prevent damage from subsequent removal during redecoration. Before applying primer-sealer or final decorations, the joint treatment must be completely dry.

Applicable Standards and References:

- ASTM C 840
- GA-216
- GA-214

See [ProRoc Install Like the Pros, Gypsum Board Installation Guide](#) for complete installation instructions.

Other Resources:

[GA-216 "Application and Finishing of Gypsum Panel Products"](#)

[GA-214 "Recommended Levels of Gypsum Board Finish"](#)

WARRANTY

Please see our [Gypsum Board Limited Warranty](#) for more information.

GREEN INFORMATION

CertainTeed is dedicated to employing practices that conserve resources:

- The gypsum board's face paper (both front and back) is made from of 100% recycled materials.
- Synthetic or "by-product" gypsum accrued in the process of flue gas desulphurization (FGD) at coal-fired power plants is used wherever sources are available. Three



- manufacturing plants use 100% synthetic gypsum—Toronto, Ontario; Moundsville, West Virginia; and Carrollton, Kentucky. The total recycled content for these plants is 96%.
- In-plant scraps are recycled back into the manufacturing process. All 14 of our gypsum board manufacturing locations provide regional material coverage throughout North America.
 - Although LEED ratings do not presently address emissions for all building materials and how they affect indoor air quality, finished CertainTeed gypsum board has no reportable emission of VOCs (volatile organic compounds) and will have no effects on indoor air quality.

Please see our [Gypsum Green Building Standards](#) for complete information.