



PROROC® LITE SAND SETTING COMPOUNDS 18 LB. BAGS

PROUDLY OFFERED BY YOUR LOCAL [KNEZ BUILDING MATERIALS SUPPLIER](#).

OVERVIEW

Knez Inc. is pleased to carry ProRoc® Brand LITE Sand Setting Compounds. These are sandable, lightweight, chemically setting powders used to pre-fill joints, embed joint tape and conceal joints, fasteners and trim accessories on gypsum wallboard. The compounds may also be used for interior patching and repair work. They are specially formulated to harden with very little shrinkage in a prescribed time frame, making them ideal for heavy fills. Several formulations are available, with setting times from 20 minutes to 90 minutes:

ProRoc® LITE Sand 20 - 308235 Setting time 15 - 25 minutes
ProRoc® LITE Sand 45 - 308234 Setting time 40 - 55 minutes
ProRoc® LITE Sand 90 - 308233 Setting time 80 - 110 minutes

Please see the [Product Data and Submittal Sheet](#) for complete Technical Data.

TECHNICAL INFORMATION

Color: Off white

Packaging: 18 lb. (8.1 kg) Bags

Coverage: Approximate coverage is 55 lbs. (25 kg) of powder per 1000 ft² (100 m²) of drywall panel.

Storage: Rotate stock to avoid aging problems. Use within 60 days of delivery.

Store in a dry place.

Shelf Life: 12 months from production code date when stored properly.

Please see the [Product Data and Submittal Sheet](#) for complete Technical Data.

Other resources:

[ProRoc® Lite Sand Sell Sheet](#)

[Finishing Brochure](#)

[MSDS - Ready-Mix](#)

INSTALLATION

JOIN FINISHING:

Three coats of compound are typically used to finish wallboard joints. The first coat is to embed the tape, the second to cover the tape, and the third to finish the joint. ProRoc Sandable Setting-Type Compound is suited for the first two of these coats. Although it is recommended that the final coat consist of a ready-mix product, Sandable Setting-Type Compounds may still be used in this capacity.



It is recommended to use fiberglass mesh tape for joint reinforcement. Apply the first coat to the joint in a band, approximately 2-1/2" in width. Place ProRoc mesh tape, centered over joint, and embed with a broad knife. Allow to set, adhering to manufacturer specifications.

PRECAUTIONS:

- These compounds generate a significant amount of heat as they harden. Prevent burns by keeping the compound away from exposed skin throughout the hardening process.
- Do not apply or re-mix after the product has started to set.
- Ensure the surface is clean and dry before applying the compound.
- Use is limited for above grade applications.
- When mixing and/or dry sanding, wear safety glasses and dust mask approved by NIOSH/MSHA.
- Keep out of reach of children.

SANDING:

Allow the compound to thoroughly dry before sanding. Use 120 grit sand-paper and a hand or pole sander. Do not sand the surface of the wallboard paper. Follow the precautions stated above.

See [Install Like the Pros Installation Guide](#) or the [Product Data and Submittal Sheet](#) for complete installation instructions.

WARRANTY

Since methods and condition of application such as temperature, humidity and over thinning are beyond our control, CertainTeed Gypsum, Inc. (CertainTeed) will not be responsible for the failure of this product when not used according to directions and specifications and accepted standards of procedure inherent in drywall application; or when reasonable allowance is not made by the user for adverse weather and job conditions. However, if this product proves to be defective, maximum liability shall be limited to replacement of the material only or refund of the purchase price. This shall be the full limit whatsoever of CertainTeed's liability. All claims shall be submitted in writing to CertainTeed within thirty days from the date of discovery. State or federal laws may provide rights in addition to this warranty that cannot be modified or excluded.

PDF: [Finishing Limited Warranty](#)

Contact Knez Inc. about ordering this product for your next project.

(Phone: 503-620-6142)

